



Welder/Pipelayer

Challenger Combo Tractor



SL3CH HYDRAULIC PIPELAYER ATTACHMENT:

- Two (2) hydraulic planetary winches.
- 15 foot boom.
- Two (2) speed load line.

Cat Challenger Features:

- Mobil-Trac undercarriage (rubber tracks for on and off road travel).
- Differential steering—full power and spin turns.
- 18 MPH travel speed
- 285 horsepower.
- Heated cab-ROPS

WELDER PACKAGE

- Four (4) welding machines.
- Newage alternator (100 kw).
- Low frequency shut off.
- Quincy 350 compressor with 120 gallon tank.
- Six (6) electrical outlets.
- Bottle rack for 6 bottles
- Two (2) storage boxes with locking latch

Features:

- Versatility and top quality performance.
- No surging when other welders start and stop.
- The right welders for every specification.

Shipping Dimensions	Rear Package		Boom/Bumper	
	Length	Width	Height	Weight
Length	90 in.	2.29 m	174 in.	4.42 m
Width	90 in.	2.29 m	60 in.	1.52 m
Height	88 in.	2.24 m	58 in.	1.47 m
Weight	7,400 lbs.	3.357 kg	1,593 lbs.	723 kg

Options:

- (5) Welders—125 kw.
- Optional Welders—Miller XMT-308, Lincoln DC-400, STT-II
- Hydraulic knuckleboom crane (in place of pipelayer).
- 50 Hz system.
- Lima Marathon alternator.
- 8' boom extension—6,000 lb. capacity.
- 6' boom extension—6,000 lb. capacity.
- Folding boom.
- Quick coupling outlets for welders.