



Challenger Trailer

Model CPT-20 and CPT-30



CPT-20 Pipe Trailer



CPT-30 Pipe Trailer

These Challenger Services trailers utilize the Steel Track design providing more flotation and resistance to rock and stump damage than rubber tires.

Ground Pressure—

Track Width

24 inches (CPT-20)

30 inches (CPT-30)

Empty

3.9 psi

3.0 psi

Max. rated load

12.4 psi

11.8 psi

FEATURES

- Handle pipe up to 60 feet long.
- The bolsters are spaced 33 feet apart.
- Quick adjustable saddle width with slide control and chain lock for varying pipe diameter.
- Two 4" strap winches on each end to keep load from shifting.
- Approximately 12 psi ground pressure fully loaded: CPT-20/40,000 lbs. and CPT-30/60,000 lbs.
- Maximum towing speed—6 mph.
- Excellent performance in mud, dirt, sand, snow and more.

Specifications

- Track gauge
- Track length CL to CL
- Ground clearance
- Overall length
 - frame only
 - frame and hitch

Overall height

- Overall width
- Weight
- Shipping Length
- Maximum inside dimension between bolsters (8" up from crossbeam)

CPT-20

5 ft. 4 in. (1.63 m)

4 ft. 1 in. (1.24 m)

1 ft 3½ in. (.039 m)

39 ft. (11.89 m)

44 ft. 6 in. (13.56 m)

5 ft. (1.52 m)

7 ft. 4 in. (2.24 m)

18,500 lbs. (8,392 kg)

39 ft. (11.89 m)

7 ft. (2.13 m)

CPT -30

4 ft. 10 in. (1.47 m)

4 ft. 8½ in. (1.44 m)

1 ft. 3 in. (.38 m)

39 ft. (11.89 m)

44 ft. 6 in. (13.56 m)

5 ft. (1.52 m)

7 ft. 4 in. (2.24 m)

20,250 lbs. (9,185 kg)

39 ft. (11.89 m)

7 ft. (2.13 m)



CHALLENGER SERVICES
4530 South Jackson Avenue
Tulsa, Oklahoma 74107 USA

Phone: (918) 447-0055
Fax: (918) 447-0067

email: sales@challengerservices.com
www.challengerservices.com